

# DOCKLITE

# DL10



- For DR/DT/DK Series only



- Designed for more connectivity possibilities and flexibilities.



Version: V1.0.2

- Specifications subject to change without notice.
- Copyright© 2023, MilDef Crete Inc. and MilDef Crete Australasia Pty Ltd.
- All rights reserved. No part of this publication may be reproduced and modified without the written permission of MilDef Crete Inc. and MilDef Crete Australasia Pty Ltd.
- All product and company names are trademarks or registered trademarks of their respective holders.

**MilDef Crete Inc.**

7 F, No. 250, Sec. 3, Pei Shen Rd., Shen Keng District, New Taipei City 22204, Taiwan (R.O.C.)  
Tel: 866-2-2662-6074 Fax: 866-2-2664-2662

[www.mildefcrete.com](http://www.mildefcrete.com)

**MilDef Crete Australasia Pty Ltd**

Level 5, 7 Eden Park Dr, Macquarie Park, NSW 2113, Australia.

Tel: +61 2 8527 2542

[www.mildefcrete.com.au](http://www.mildefcrete.com.au)

# DOCKLITE

## DL10

### Appearance

### Operating Instruction

1. Align the tablet with Docklite.
2. Attach the Docklite.
3. Tighten the screws.

## Features

External Ports	
<b>Connector ports (From left to right)</b>	– Audio (Microphone, Speaker)
	– VGA DB15 x 1
	– Optional GLAN RJ45 x 1
	– Serial Port DB9 x 2
	– USB 2.0 x 4 (Type-A x 2, Type-M x 2)

Electronic characteristics (DC Input)	
<b>DC Input Range</b>	–12 ~ 32V
<b>Standard Connector</b>	– DC-In 2 pin
<b>Optional Connector</b>	– Military 3-pin

Physical Characteristics	
<b>Dimension</b>	– 250 (L) x 37 (W) x 61 (H) mm
<b>Weight</b>	– Approx. 450g

Environmental Ratings and Certifications	
<b>Operating Temperature</b>	– 0°C ~ +50°C
<b>Storage Temperature</b>	– -40°C ~ +70°C
<b>Certifications</b>	– CE – FCC